

ARTICOLO / ARTICLE ACOUSTIC

UTILIZZO CONSIGLIATO/ SUITABLE FOR Tendaggio / Curtaining

CARATTERISTICHE / TECHNICAL SPECIFICATIONS

COMPOSIZIONE / COMPOSITION	COLORE / COLOUR	ALTEZZA / WIDTH	PESO / WEIGHT	CLASSE IGNIFUGA	FLAME RETARDANT
TREVIRA CS 91% PL 9%	Tinto in filo / Yarn dyed	↕ 330 cm	366gml / 111 g/m ²	Certificazioni Trevira cs B1(D), M1(F), EN 13773(EU)	Certifications B1(D), M1(F), EN 13773(EU)

VARIAZIONI DIMENSIONALI A SECCO / DRY DIMENSIONAL STABILITY

	ORDITO/ WARP	TRAMA / WEFT
Procedura interna / Internal procedure	≤ -1,0%	≤ -1,5%

LAVABILITA' / CLEANING

ISTRUZIONI AL LAVAGGIO / CLEANING INSTRUCTIONS



made in Italy

 AGENA
 PRO
SOLIDITA' DEL COLORE / COLOUR FASTNESS

LAVAGGIO A SECCO / DRY CLEANING	scala range	LAVAGGIO AD UMIDO / WET WASHING	scala range	LUCE / LIGHT	scala range
UNI EN ISO 105 D01 4/5	1-5	UNI EN ISO 105 C06 4/5	1-5	UNI EN ISO 105 B02 4/5	1-8

PROPRIETA' / PROPERTIES

Tenda acustica qw: 0.5 - UNI EN ISO 11654
Acoustic è una tenda antifiama acustica.

Acoustic sheer qw: 0.5 - UNI EN ISO 11654
Acoustic is a fire retardant acoustic sheer.

made in Italy

 AGENA
 PRO